
K-DBV MANO 1/4"

Pressure limiting valves size 1/4



Properties			
Design	Spring-loaded, non-return diaphragm valve with adjustable opening pressure		
Media temperature	max. 60 °C		
Ambient temperature	Max. 60 °C		
Sealant	NBR		
Spring bonnet	POM/brass		
Housing	Die-cast zinc, painted silver		
Diaphragm	NBR		





Note

Further information on request

Description

Manually adjustable overflow valves. For protecting pneumatic systems against damage caused by excess pressure.

Item

Thread	Control range	Α	В	С	D
		(mm)		(mm)	(mm)
G 1/4	0.1 - 2.0 bar	43,0	70.0 mm	10,0	60,0
G 1/4	0.1 - 3.0 bar	43,0	70.0 mm	10,0	60,0
G 1/4	0.15 - 7.0 bar	43,0	70.0 mm	10,0	60,0
G 1/4	0.5 - 10.0 bar	43,0	70.0 mm	10,0	60,0
	G 1/4 G 1/4 G 1/4	G 1/4 0.1 - 2.0 bar G 1/4 0.1 - 3.0 bar G 1/4 0.15 - 7.0 bar	G 1/4 0.1 - 2.0 bar 43,0 G 1/4 0.1 - 3.0 bar 43,0 G 1/4 0.1 - 3.0 bar 43,0 G 1/4 0.15 - 7.0 bar 43,0	G 1/4 0.1 - 2.0 bar 43,0 70.0 mm G 1/4 0.1 - 3.0 bar 43,0 70.0 mm G 1/4 0.15 - 7.0 bar 43,0 70.0 mm	(mm) (mm) G 1/4 0.1 - 2.0 bar 43,0 70.0 mm 10,0 G 1/4 0.1 - 3.0 bar 43,0 70.0 mm 10,0 G 1/4 0.15 - 7.0 bar 43,0 70.0 mm 10,0

Spare parts			
K-HALTERBAUSATZ	Holder		
K-SCHALTTAFELMUTTER	Nut		
K-VERSCHLEI-SATZ	Set of wearing parts		
K-SCHALLDAE SINTERBR AG 569	Silencers, sintered bronze, flat type with male thread, 569 Series		
K-GERAETESTECKER	Coupling socket		