K-FLASCHENDRUCKR 200 N GASE

Cylinder pressure regulators, cylinder pressure 200 bar, for non-flammable gases

Properties

Pressure gauge for contents	0 - 200/315 bar (max. cylinder pressure 200 bar), 0 - 300/400 bar (max. cylinder pressure 300 bar), 0 - 18/40 bar for acetylene
Material	Hot pressed brass
Cylinder connection	Nut 3/4



Note

Further information on request

Description

Single-stage type of construction acc. to DIN EN ISO 2503, with shut-off valve and safety valve as well as pressure gauges for the cylinder contents and working pressure.

Item

Identification	gas type	Operating pressure
K- 07 25 07 11	Oxygen	0 - 10,0 bar
K- 07 25 07 12	Oxygen	0 - 20,0 bar
K- 07 25 07 14	Compressed air	0 - 10,0 bar
K- 07 25 07 15	Compressed air	0 - 20,0 bar
K- 07 25 07 16	Nitrogen	0 - 10,0 bar
K- 07 25 07 17	Nitrogen	0 - 20,0 bar
K- 07 25 07 18	Carbon dioxide	0 - 10,0 bar
K- 07 25 07 19	Carbon dioxide	0 - 20,0 bar
K- 07 25 07 20	Argon/helium	0 - 10,0 bar

Spare parts

K-MANO SCHWEISSTECHNIK	Content pressure gauge
K-MANO SCHW	Pressure gauges for welding
K-SCHUTZKAPPE MANOMETER	Protective covers

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.