
## K-HOCHLEIST DRUCKREGLER

Heavy-duty pressure regulators



Properties		
Input pressure	Max. 25 bar	
Media temperature	max. 60 °C	
Ambient temperature	Max. 60 °C	
Flow rate	50000 l/min	
Sealant	NBR	
Housing	Aluminium, painted silver	
Flow rate measurement	At P1 = 8 bar, P2 = 6 bar and pressure drop Δp = 1 bar	





## Note

Further information on request

## **Description**

Diaphragm pressure regulators, independent of inlet pressure, with internal pilot control and self-relieving designfor very high flow rates. Separate indication of input and working pressure on two pressure gauges. The pressure setting can be locked by pushing the knob down. We recommend always using these controllers in conjunction with our K-07250607 and K-07250609 filters.

Item					
Identification	Thread	Control range	A (mm)	В	DN
K- 07 25 08 03	G 1 1/2	0.1 - 3 bar	188,0	261.0 mm	50
K- 07 25 08 04	G 1 1/2	0.2 - 6 bar	188,0	261.0 mm	50
K- 07 25 08 05	G 1 1/2	0.5 - 10 bar	188,0	261.0 mm	50
K- 07 25 08 06	G 1 1/2	0.5 - 16 bar	188,0	261.0 mm	50
K- 07 25 08 07	G 2	0.1 - 3 bar	160,0	261.0 mm	50
K- 07 25 08 08	G 2	0.2 - 6 bar	160,0	261.0 mm	50
K- 07 25 08 09	G 2	0.5 - 10 bar	160,0	261.0 mm	50
K- 07 25 08 10	G 2	0.5 - 16 bar	160,0	261.0 mm	50

Spare parts	
K-VERSCHLEI-SATZ	Set of wearing parts
K-LOESBARE DOPPELNIPPEL MS	Double nipples