
## K-FI MIKRO PC-BEHAEL MULTIFIX MINI

Micro-filters with polycarbonate bowl



Properties			
Input pressure	Max. 16 bar		
Media temperature	max. 60 °C		
Ambient temperature	Max. 60 °C		
Filter rating	0,01 μm		
Efficiency	99.999 %		
Sealant	NBR		
Filter insert	Borosilicate-POM		
Housing	Die-cast zinc		
Drain valve	Semi-automatic		
Flow rate measurement	FM at P1 = 6 bar and pressure drop Δp = 0.09 bar		





## Note

If several devices in the »multifix-mini« Series are assembled together, the maximum working pressure is 12 bar. Further information on request

## Description

Micro-filters for compliance with strict compressed air purity requirements. Suitable for all applications where standard filters do not afford the desired efficiency.

Item								
Identification	Thread	Flow rate (L/min)	A (mm)	В	C (mm)	D (mm)	DN	
K- 07 25 10 54	G 1/8	230	40,0	114.8 mm	12,3	102,5	5	
K- 07 25 10 56	G 1/4	450	40,0	138.1 mm	12,3	125,8	5	

Spare parts			
K-AUTOMAT ABLASSVENTIL	Automatic drain valve		
K-KOPPEL PAKET MEHR	Counling packet		