


K-FI REGL H ABLV VA

Filter regulators



Properties	
Input pressure	Max. 30 bar
Media temperature	max. 130 °C
Ambient temperature	Max. 60 °C
Flow rate	2500 l/min
Pore size in filter element	50 µm
Sealant	FKM
Diaphragm	PTFE on NBR base
Material	stainless steel 1.4404 (AISI 316L)
Drain valve	Manual drain valve
Flow rate measurement	At P1 = 10 bar, P2 = 5 bar and pressure drop $\Delta p \leq 1$ bar



Note

Further information on request

Description

Stainless steel filter regulators with self-relieving (not for liquid media) containing no non-ferrous metals for use in the food processing, chemical, mining, plant construction and special machinery industries as well as in the medical technology.

Ordering information

With filter element 5 µm available on request. Without self-relieving design (for liquids) available on request. With semi- or fully automatic drain valve on request. With NPT threads available on request.

Item					
Identification	Thread	Control range	A (mm)	B	C (mm)
K- 07 25 06 52	G 1/4	1.0 - 15.0 bar	65,0	250.0 mm	125,0
K- 07 25 06 51	G 1/2	1.0 - 15.0 bar	80,0	260.0 mm	127,0

Spare parts

K-HALTERBAUSATZ EDELSTAHL	Holder
K-MANO	Pressure gauges (CrNi steel type / connection on rear)
K-VERSCHLEI-SATZ	Set of wearing parts