
K-NEBELOEL PC-BEHAEL SCHUTZK HANSA HANSA FLEX



Properties		
Input pressure	0.5 - 16 bar	
Temp. range	-10 °C to +50 °C	
Media	Compressed air	
Sealant	NBR	
Connection thread	Material: Die-cast zinc	
Container	Polycarbonate (with bayonet lock)	
Housing	Material: Grivory® (PA 66)	
Protective cage	Polyamide	
Dropper	PA	
Oil grade	CL 32 acc. to DIN 51517 - ISO VG 32	
Flow rate measurement	At P2 = 6 bar, pressure drop Δp = 1 bar	



Note

Further information on request

Description

Oil-mist lubricators with excellent flow rates in modern design. These devices can be used to top up oil automatically. A hose must be connected to the threaded nipple on the oil bowl for this purpose. When the oil filling button on the top of the device is pressed, a Venturi nozzle opens and sucks oil into the bowl under vacuum.

Item					
Identification	Thread	Flow rate	А	В	С
		(L/min)	(mm)		(mm)
K- 07 25 08 79	G 1/4	2800	52,0	183.0 mm	62,2
K- 07 25 08 80	G 3/8	2800	52,0	183.0 mm	62,2
K- 07 25 08 81	G 3/8	8000	63,0	208.2 mm	69,7
K- 07 25 08 82	G 1/2	8000	63,0	208.2 mm	69,7
K- 07 25 08 77	G 3/4	16000	85,0	270.4 mm	87,9
K- 07 25 08 78	G 1	16000	85,0	270.4 mm	87,9

Spare parts		
K-HALTERBAUSATZ HANSA	Holder HANSA	
K-ERSATZBEHAELTER HANSA POLY	Spare tank HANSA polycarbonat	
K-TROPFAUFSATZ HANSA	Drip attachment HANSA	