


K-PRAEZI DRG DRUCKVER HANSA

Precision pressure regulators with continuous pressure supply



Properties

Input pressure	Max. 16 bar
Temp. range	-10 °C to +50 °C
Media	Compressed air
Connection thread	Material: Die-cast zinc
Housing	Material: Grivory® (PA 66)
Diaphragm	NBR
Internal air consumption	2.6 l/min at P2 = 6 bar (depending on secondary pressure)
Flow rate measurement	At P1 = 10 bar, P2 = 6.3 bar and pressure drop $\Delta p = 1$ bar



Note

Further information on request

Description

Precision diaphragm pressure regulators with self-relieving design and excellent flow rates in modern design for mounting side by side.
By assembling two or more controllers together, it is possible to supply several working air circuits with different pressures via a single supply line.

Ordering information

The price does not include a key lock. Please order separately.

Item	Identification	Thread	Control range	Flow rate (L/min)	A (mm)	B	C (mm)
	K- 07 25 09 66	G 1/4	0.1 - 1 bar	2200	52,0	128.5 mm	95,5
	K- 07 25 09 67	G 1/4	0.1 - 2 bar	2200	52,0	128.5 mm	95,5
	K- 07 25 09 68	G 1/4	0.2 - 4 bar	2200	52,0	128.5 mm	95,5
	K- 07 25 09 69	G 1/4	0.5 - 8 bar	2200	52,0	128.5 mm	95,5
	K- 07 25 09 70	G 1/4	0.5 - 10 bar	2200	52,0	128.5 mm	95,5
	K- 07 25 09 71	G 3/8	0.1 - 1 bar	2700	52,0	128.5 mm	95,5
	K- 07 25 09 72	G 3/8	0.1 - 2 bar	2700	52,0	128.5 mm	95,5
	K- 07 25 09 73	G 3/8	0.2 - 4 bar	2700	52,0	128.5 mm	95,5
	K- 07 25 09 74	G 3/8	0.5 - 8 bar	2700	52,0	128.5 mm	95,5
	K- 07 25 09 75	G 3/8	0.5 - 10 bar	2700	52,0	128.5 mm	95,5
	K- 07 25 09 76	G 3/8	0.1 - 1 bar	4300	63,0	149.5 mm	110,0
	K- 07 25 09 77	G 3/8	0.1 - 2 bar	4300	63,0	149.5 mm	110,0
	K- 07 25 09 78	G 3/8	0.2 - 4 bar	4300	63,0	149.5 mm	110,0
	K- 07 25 09 79	G 3/8	0.5 - 8 bar	4300	63,0	149.5 mm	110,0
	K- 07 25 09 80	G 3/8	0.5 - 10 bar	4300	63,0	149.5 mm	110,0
	K- 07 25 09 81	G 1/2	0.1 - 1 bar	5000	63,0	149.5 mm	110,0
	K- 07 25 09 82	G 1/2	0.1 - 2 bar	5000	63,0	149.5 mm	110,0
	K- 07 25 09 83	G 1/2	0.2 - 4 bar	5000	63,0	149.5 mm	110,0
	K- 07 25 09 84	G 1/2	0.5 - 8 bar	5000	63,0	149.5 mm	110,0
	K- 07 25 09 85	G 1/2	0.5 - 10 bar	5000	63,0	149.5 mm	110,0

Accessories

K-STECKSCHLOSS Key lock

Spare parts

K-HALTERBAUSATZ HANSA	Holder HANSA
K-SCHALTAFELMUTTER HANSA	Nut HANSA
K-DICHTSATZ HANSA	Set of seals HANSA