

# K-ANFAV MULTIFIX

## Start-up valves

### Properties

<b>Input pressure</b>	Min. 2 bar, max. 16 bar
<b>Media temperature</b>	max. 60 °C
<b>Ambient temperature</b>	Max. 60 °C
<b>Sealant</b>	NBR
<b>Housing</b>	Die-cast zinc, Aluminium for G 3/4 and G 1 variant
<b>Flow rate measurement</b>	At P1 = 6 bar and pressure drop $\Delta p = 1$ bar



### Note

Further information on request

### Description

Seat valves operated by secondary pressure for controlled pressurisation of pneumatic systems. The full cross-section of the regulator is opened at 50% of the input pressure. The filling time can be altered by turning the adjusting screw.

### Item

Identification	Thread	Flow rate (L/min)	A (mm)	B	D (mm)
K- 07 25 11 54	G 1/4	1000	47,8	54.2 mm	26,8
K- 07 25 11 55	G 1/2	4000	68,8	71.6 mm	35,1
K- 07 25 19 34	G 3/4	12000	99,7	104.0 mm	52,0
K- 07 25 19 35	G 1	12000	99,7	104.0 mm	52,0

### Spare parts

K-KOPPELPAKET MEHR	Coupling packet
K-KOPPELPAKET SCHMA	Coupling packet