

K-FI PC-BEHÄLTER MULTIFIX

Filters with polycarbonate bowl

HANSA FLEX

Properties

| | |
|------------------------------------|--|
| Input pressure | Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl) |
| Media temperature | max. 60 °C |
| Ambient temperature | Max. 60 °C |
| Pore size in filter element | 5 µm (BG 1 / BG 2), 40 µm (BG 3) |
| Housing | Die-cast zinc, Aluminium for G 1 variant |
| Drain valve | Semi-automatic |
| Flow rate measurement | At P1 = 6 bar and pressure drop $\Delta p = 1$ bar |



Note

Further information on request

Description

Centrifugal separators with a sintered filter element.

Item

| Identification | Thread | Flow rate (L/min) | A (mm) | B | C (mm) | D (mm) | DN | Size |
|----------------|--------|-------------------|--------|----------|--------|--------|----|------|
| K- 07 25 00 46 | G 1/4 | 2100 | 47,8 | 152.1 mm | 27,0 | 125,1 | 6 | 1 |
| K- 07 25 00 49 | G 3/8 | 2100 | 47,8 | 152.1 mm | 27,0 | 125,1 | 10 | 1 |
| K- 07 25 00 52 | G 1/2 | 4000 | 68,8 | 181.8 mm | 34,5 | 147,3 | 15 | 2 |
| K- 07 25 00 55 | G 3/4 | 4000 | 68,8 | 181.8 mm | 34,5 | 147,3 | 20 | 2 |
| K- 07 25 00 58 | G 1 | 8000 | 100,0 | 305.8 mm | 52,0 | 253,8 | 25 | 3 |

Spare parts

| | |
|---------------------------------|---------------------------|
| K-HALTERBAUSATZ MULTIFIX | Holder |
| K-KOPPELPAKET MEHR | Coupling packet |
| K-KOPPELPAKET SCHMA | Coupling packet |
| K-METALLBEHÄLTER OELER MULTIFIX | Metal tank oiler |
| K-PC-BEHÄLTER FILTER MULTIFIX | Polycarbonate tank filter |
| K-SCHUTZKORB G | Protective cage |
| K-FILTERELEMENT | Filter element |
| K-AUTOMAT ABLASSVENTIL | Automatic drain valve |