


# K-FI PC-BEHAELTER SCHUTZK MULTIFIX

Filters with polycarbonate bowl and bowl guard

**HANSA FLEX**

## Properties

<b>Input pressure</b>	Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)
<b>Media temperature</b>	max. 60 °C
<b>Ambient temperature</b>	Max. 60 °C
<b>Pore size in filter element</b>	5 µm (BG 1 / BG 2), 40 µm (BG 3)
<b>Housing</b>	Die-cast zinc, Aluminium for G 1 variant
<b>Drain valve</b>	Semi-automatic
<b>Flow rate measurement</b>	At P1 = 6 bar and pressure drop $\Delta p = 1$ bar



## Note

Further information on request

## Description

Centrifugal separators with a sintered filter element.

## Item

Identification	Thread	Flow rate (L/min)	A (mm)	B	C (mm)	D (mm)	DN	Size
K- 07 25 00 48	G 1/4	2100	47,8	152.1 mm	27,0	125,1	6	1
K- 07 25 00 51	G 3/8	2100	47,8	152.1 mm	27,0	125,1	10	1
K- 07 25 00 54	G 1/2	4000	68,8	181.8 mm	34,5	147,3	15	2
K- 07 25 00 57	G 3/4	4000	68,8	181.8 mm	34,5	147,3	20	2
K- 07 25 00 60	G 1	8000	100,0	305.8 mm	52,0	253,8	25	3

## Spare parts

K-HALTERBAUSATZ MULTIFIX	Holder
K-KOPPELPAKET MEHR	Coupling packet
K-KOPPELPAKET SCHMA	Coupling packet
K-METALLBEHAELTER OELER MULTIFIX	Metal tank oiler
K-PC-BEHAELTER FILTER MULTIFIX	Polycarbonate tank filter
K-SCHUTZKORB G	Protective cage
K-FILTERELEMENT	Filter element
K-AUTOMAT ABLASSVENTIL	Automatic drain valve