

K-NEBELOELER PC-BEHAEL S MULTIFIX

Oil-mist lubricators with polycarbonate bowl and bowl guard

HANSA FLEX

Properties

Input pressure	Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)
Media temperature	max. 60 °C
Ambient temperature	Max. 60 °C
Sealant	NBR
Housing	Die-cast zinc, Aluminium for G 1 variant
Dropper	PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)
Drain valve	Manual
Oil grade	CL 32 acc. to DIN 51517 - ISO VG 32
Flow rate measurement	At P1 = 6 bar and pressure drop $\Delta p = 1$ bar



Note

Further information on request

Description

Proportional lubricators, oil can be filled under pressure.

Item

Identification	Thread	Flow rate (L/min)	A (mm)	B	C (mm)	D (mm)	DN	Size
K- 07 25 00 93	G 1/4	1900	47,8	167.8 mm	58,0	109,8	6	1
K- 07 25 00 96	G 3/8	1900	47,8	167.8 mm	58,0	109,8	10	1
K- 07 25 00 99	G 1/2	5000	68,8	198.6 mm	66,1	132,5	15	2
K- 07 25 01 02	G 3/4	5000	68,8	198.6 mm	66,1	132,5	20	2
K- 07 25 01 05	G 1	18000	100,0	324.3 mm	82,7	241,6	25	3

Spare parts

K-HALTERBAUSATZ MULTIFIX	Holder
K-KOPPELPAKET MEHR	Coupling packet
K-KOPPELPAKET SCHMA	Coupling packet
K-METALLBEHAELTER OELER MULTIFIX	Metal tank oiler
K-PC-BEHAELTER FILTER MULTIFIX	Polycarbonate tank filter
K-SCHUTZKORB G	Protective cage
K-TROPFAUFSATZ POLYCARBO 1	Drip attachment polycarbonate
K-TROPFAUFSATZ METALL	Drip attachment metal