

K-VT BREIT MULTIFIX

Manifolds - wide design

HANSA FLEX

Properties

| | |
|-----------------------|--|
| Input pressure | Max. 16 bar |
| Media temperature | max. 60 °C |
| Ambient temperature | Max. 60 °C |
| Sealant | NBR |
| Housing | Die-cast zinc |
| Flow rate measurement | At P1 = 6 bar and pressure drop $\Delta p = 1$ bar |



Note

Flow rate l/min at P → A
Further information on request

Description

Wide or narrow, four-way manifolds.

Item

| Identification | Outlets | Thread | Flow rate (L/min) | A (mm) | B | C (mm) | Size |
|----------------|------------------|--------|-------------------|--------|---------|--------|------|
| K- 07 25 11 73 | 4 x 1/4 | G 1/4 | 2500 | 47,8 | 52.0 mm | 26,0 | 1 |
| K- 07 25 11 74 | 4 x 1/4 | G 3/8 | 2500 | 47,8 | 52.0 mm | 26,0 | 1 |
| K- 07 25 11 75 | 2 x 1/4, 2 x 1/2 | G 1/2 | 11000 | 68,8 | 67.0 mm | 33,5 | 2 |
| K- 07 25 11 76 | 2 x 1/4, 2 x 1/2 | G 3/4 | 11000 | 68,8 | 67.0 mm | 33,5 | 2 |

Accessories

| | |
|-------------------------------------|---|
| K-DRS WECHSELKONTAK ANFLANSCHBAR DS | Pressure switches, changeover type, suitable for flange mounting K-07302861 |
| K-ZUBEH HANSA | Accessories for pressure switch HANSA |

Spare parts

| | |
|---------------------|-----------------|
| K-KOPPELPAKET MEHR | Coupling packet |
| K-KOPPELPAKET SCHMA | Coupling packet |