
K-DRG DRVS MULTIFIX MINI

Pressure regulators with pressure supply at both ends



Properties				
Input pressure	Max. 16 bar			
Media temperature	max. 60 °C			
Ambient temperature	Max. 60 °C			
Sealant	NBR			
Spring bonnet	POM-brass			
Housing	Die-cast zinc			
Flow rate measurement	At P1 = 8 bar, P2 = 6 bar and pressure drop Δp = 1 bar			





Note

Further information on request

Description

Diaphragm pressure regulators with self-relieving design for mounting side by side. The pressure setting can be locked by pushing the button down.
 Sy assembling two or more controllers together, it is possible to supply several working air circuits with different output pressures via a single supply line.

Ordering information

The port for the output pressure (P2) is on the rear! K-07250028: G 1/8. Lockable pressure regulator: K-07250027. If several devices in the »multifix-mini« Series are assembled together, the maximum working pressure is 12 bar.

Item									
Identification	Thread	Control range	Flow rate	A (mm)	В	C (mm)	D (mm)	DN	Size
K- 07 25 00 28	G 1/4	0.1 - 3 bar	1200	40,0	85.0 mm	63,0	22,0	5	0
K- 07 25 00 29	G 1/4	0.2 - 6 bar	1200	40,0	85.0 mm	63,0	22,0	5	0
K- 07 25 00 27	G 1/4	0.5 - 10 bar	1200	40,0	85.0 mm	63,0	22,0	5	0

Spare parts	
K-HALTERBAUSATZ	Holder
K-SCHALTTAFELMUTTER	Nut
K-KOPPELPAKET MEHR	Coupling packet
K-VERSCHLEI-SATZ	Set of wearing parts