
K-FI PC-BEHAEL H ABLV MULTIFX MINI

Filters with polycarbonate bowl and semi-automatic drain valve

Properties

Input pressure	Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)
Media temperature	max. 60 °C
Ambient temperature	Max. 60 °C
Flow rate	1000 l/min
Pore size in filter element	5 µm
Housing	Die-cast zinc
Drain valve	Semi-automatic
Flow rate measurement	At P2 = 6 bar and pressure drop Δp = 1 bar





Note

If several devices in the »multifix-mini« Series are assembled together, the maximum working pressure is 12 bar.
Further information on request

Description

Centrifugal separators with a sintered filter element.

Item

Identification	Thread	A (mm)	B	C (mm)	D (mm)	DN	Size
K- 07 25 00 42	G 1/8	40,0	114.8 mm	12,3	102,5	5	0
K- 07 25 00 44	G 1/4	40,0	114.8 mm	12,3	102,5	5	0

Spare parts

K-AUTOMAT ABLASSVENTIL	Automatic drain valve
K-KOPPELPAKET MEHR	Coupling packet
K-ERSATZBEHAELTER MULTI MINI	Spare tank »multifix-mini« & »standard-mini«
K-PC-BEHAELTER FILTER MULTIFIX	Polycarbonate tank filter
K-FILTERELEMENT	Filter element

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.