



# K-3/2-BKR MULTIFIX MINI

Ball valves

**HANSA FLEX**

## Properties

<b>Media temperature</b>	max. 60 °C
<b>Ambient temperature</b>	Max. 60 °C
<b>Operation</b>	Twist knob, rotatable 90°
<b>Flow rate</b>	1800 l/min
<b>Vent port</b>	Silencer G 1/4
<b>Sealant</b>	NBR
<b>Housing</b>	Die-cast zinc
<b>Flow rate measurement</b>	At P1 = 6 bar and pressure drop $\Delta p = 1$ bar



## Note

If several devices in the »multifix-mini« Series are assembled together, the maximum working pressure is 12 bar.  
Further information on request

## Description

Rotary switch can be turned 90°, lockable, with relief port

## Item

Identification	Thread	A (mm)	B	C (mm)	D (mm)	Size
K- 07 25 11 56	G 1/8	40,0	57.6 mm	37,6	20,0	0
K- 07 25 11 57	G 1/4	40,0	57.6 mm	37,6	20,0	0

## Spare parts

K-KOPPELPAKET MEHR	Coupling packet
K-AUTOMAT ABLASSVENTIL	Automatic drain valve
K-SCHALLDAE SINTERBR SCHLITZ	Silencers, sintered bronze, slotted