
K-SCHALTVENTILE 3/2 MULTIFIX MINI

On-off valves (3/2-way valves)



Properties			
Input pressure	Min. 2 bar, max. 10 bar		
Media temperature	max. 60 °C		
Ambient temperature	Max. 60 °C		
Electrical connection	Device plug PG 9, type B, EN 175301-803		
Protection IP	IP 65 (P 54) acc. to DIN 40050		
Flow rate	1600 l/min		
cyclic duration relative	100 %		
Vent port	Silencer G 1/4		
Sealant	NBR		
Housing	Die-cast zinc		
Flow rate measurement	At P1 = 6 bar and pressure drop Δp = 1 bar		





Note

If several devices in the »multifix-mini« Series are assembled together, the maximum working pressure is 12 bar. Further information on request

Description

Pneumatic systems or parts of systems can be switched on and off by means of anelectrical signal. When they are switched off, the system is relieved at the same time.

Item						
Identification	Thread	Solenoid	А	В	С	Size
			(mm)		(mm)	
K- 07 25 11 62	G 1/4	230 V AC, 50 Hz	45,0	29.0 mm	96,0	0
K- 07 25 11 63	G 1/4	110 V AC, 50 Hz	45,0	29.0 mm	96,0	0
K- 07 25 11 64	G 1/4	24 V DC	45,0	29.0 mm	96,0	0

Spare parts	
K-KOPPELPAKET MEHR	Coupling packet
K-GERAETESTECKER	Coupling socket
K-AUTOMAT ABLASSVENTIL	Automatic drain valve
K-MAGNETSPULE MULTIFIX	Solenoid
K-SCHALLDAE SINTERBR SCHLITZ	Silencers, sintered bronze, slotted