

# K-SCHALTVENTILE 3/2 MULTIFIX MINI

On-off valves (3/2-way valves)

**HANSA FLEX**

## Properties

<b>Input pressure</b>	Min. 2 bar, max. 10 bar
<b>Media temperature</b>	max. 60 °C
<b>Ambient temperature</b>	Max. 60 °C
<b>Electrical connection</b>	Device plug PG 9, type B, EN 175301-803
<b>Protection IP</b>	IP 65 (P 54) acc. to DIN 40050
<b>Flow rate</b>	1600 l/min
<b>cyclic duration relative</b>	100 %
<b>Vent port</b>	Silencer G 1/4
<b>Sealant</b>	NBR
<b>Housing</b>	Die-cast zinc
<b>Flow rate measurement</b>	At P1 = 6 bar and pressure drop $\Delta p = 1$ bar



## Note

If several devices in the »multifix-mini« Series are assembled together, the maximum working pressure is 12 bar. Further information on request

## Description

Pneumatic systems or parts of systems can be switched on and off by means of an electrical signal. When they are switched off, the system is relieved at the same time.

## Item

Identification	Thread	Solenoid	A (mm)	B	C (mm)	Size
K- 07 25 11 62	G 1/4	230 V AC, 50 Hz	45,0	29.0 mm	96,0	0
K- 07 25 11 63	G 1/4	110 V AC, 50 Hz	45,0	29.0 mm	96,0	0
K- 07 25 11 64	G 1/4	24 V DC	45,0	29.0 mm	96,0	0

## Spare parts

K-KOPPELPAKET MEHR	Coupling packet
K-GERAETESTECKER	Coupling socket
K-AUTOMAT ABLASSVENTIL	Automatic drain valve
K-MAGNETSPULE MULTIFIX	Solenoid
K-SCHALLDAE SINTERBR SCHLITZ	Silencers, sintered bronze, slotted