

# K-NEBELOELER PC-BEHÄLTER STANDARD

Oil-mist lubricators with polycarbonate bowl

**HANSA FLEX**

## Properties

|                              |  |
|------------------------------|--|
| <b>Input pressure</b>        | Max. 16 bar (polycarbonate bowl / bowl guard),<br>Max. 25 bar (metal bowl) |
| <b>Media temperature</b>     | max. 60 °C   |
| <b>Ambient temperature</b>   | Max. 60 °C   |
| <b>Sealant</b>               | NBR  |
| <b>Housing</b>               | Die-cast zinc, painted silver  |
| <b>Dropper</b>               | PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)                       |
| <b>Oil grade</b>             | CL 32 acc. to DIN 51517 - ISO VG 32  |
| <b>Flow rate measurement</b> | At P2 = 6 bar and pressure drop $\Delta p = 1$ bar                         |
| <b>More information</b>      | User manual on request   |



## Description

Proportional lubricators, oil can be filled under pressure.

## Item

| Identification | Thread  | Flow rate<br>(L/min) | A<br>(mm) | C<br>(mm) | D<br>(mm) | DN |
|----------------|---------|----------------------|-----------|-----------|-----------|----|
| K- 07 25 08 87 | G 1/4   | 1200                 | 50,0      | 51,0      | 118,0     | 6  |
| K- 07 25 08 90 | G 3/8   | 1200                 | 50,0      | 51,0      | 118,0     | 6  |
| K- 07 25 08 93 | G 3/8   | 2400                 | 70,0      | 51,0      | 129,5     | 10 |
| K- 07 25 08 96 | G 1/2   | 4000                 | 79,0      | 55,0      | 157,0     | 15 |
| K- 07 25 08 99 | G 3/4   | 9000                 | 102,0     | 58,0      | 160,0     | 20 |
| K- 07 25 09 02 | G 1     | 9000                 | 90,0      | 58,0      | 160,0     | 25 |
| K- 07 25 09 05 | G 1 1/4 | 9000                 | 137,0     | 70,0      | 232,0     | 40 |
| K- 07 25 09 08 | G 1 1/2 | 9000                 | 125,0     | 70,0      | 232,0     | 45 |

## Spare parts

|                                   |   |
|-----------------------------------|---|
| <b>K-HALTERBAUSATZ STANDARD</b>   | Holder  |
| <b>K-TROPFAUFSATZ POLYCARBO</b>   | Drip attachment polycarbonate                             |
| <b>K-SCHUTZKORB G</b>             | Protective cage   |
| <b>K-XV AGM MS NI</b>             | Double nipples, parallel male thread, nickel-plated brass |
| <b>K-LOESBARE DOPPELNIPPEL MS</b> | Double nipples  |
| <b>K-RD NIPPEL MS NI</b>          | Reducing nipples - nickel-plated brass                    |
| <b>K-TROPFAUFSATZ METALL</b>      | Drip attachment metal                                     |