
K-WTEH 2-TLG MET MANO TROPF STAN-MI

Service units, 2-piece with metal bowl and pressure gauge, metal sight dome



Properties			
Input pressure	Max. 16 bar (polycarbonate bowl), Max. 25 bar (metal bowl)		
Media temperature	max. 60 °C		
Ambient temperature	Max. 60 °C		
Flow rate	350 l/min (2-piece), 300 l/min (3-piece)		
Pore size in filter element	5 μm		
Sealant	NBR		
Housing	Die-cast zinc, painted silver		
Dropper	PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl)		
Drain valve	Semi-automatic for variant with polycarbonate bowl, Manual for variant with metal bowl		
Flow rate measurement	At P1 = 8 bar, P2 = 6 bar and pressure drop Δp = 1 bar		





Note

Further information on request

Description

Compact, two or three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Item								
Identification	Thread	Control range	Α	В	С	D	DN	
			(mm)		(mm)	(mm)		
K- 07 25 14 90	G 1/8	0.5 - 10 bar	85,0	167.0 mm	65,0	102,0	5	
K- 07 25 14 92	G 1/4	0.5 - 10 bar	85,0	167.0 mm	67,0	102,0	5	

Spare parts	
K-HALTERBAUSATZ	Holder
K-SCHALTTAFELMUTTER	Nut
K-ERSATZBEHAELTER MULTI MINI	Spare tank »multifix-mini« & »standard-mini«
K-PC-BEHAELTER FILTER MULTIFIX	Polycarbonate tank filter
K-VERSCHLEI-SATZ	Set of wearing parts
K-FILTERELEMENT	Filter element
K-AUTOMAT ABLASSVENTIL	Automatic drain valve
K-TROPFAUFSATZ POLYCARBO	Drip attachment polycarbonate
K-TROPFAUFSATZ METALL	Drip attachment metal
K-LOESBARE DOPPELNIPPEL MS	Double nipples
K-XV AGM MS NI	Double nipples, parallel male thread, nickel-plated brass