

# K-FI METALLBEHAELTER SICHT VARIBLOC

Filters with metal bowl incl. sight glass

**HANSA FLEX**

## Properties

|                                    |  |
|------------------------------------|--|
| <b>Input pressure</b>              | Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl) |
| <b>Media temperature</b>           | max. 50 °C   |
| <b>Ambient temperature</b>         | Max. 50 °C (polycarbonate bowl), Max. 80 °C (metal bowl)   |
| <b>Pore size in filter element</b> | 40 µm  |
| <b>Sealant</b>                     | NBR  |
| <b>Housing</b>                     | Die-cast zinc  |
| <b>Drain valve</b>                 | Manual   |
| <b>Flow rate measurement</b>       | At P1 = 6 bar and pressure drop $\Delta p = 1$ bar         |



## Note

Further information on request

## Description

Centrifugal separators with a sintered filter element. Filtration takes place in a 2-stage process comprising cyclone separation (condensate) and a PE filter element (particles). <br>Approved series in modern industrial design, with the following key benefits: Simple handling, Convenient modular assembly thanks to innovative fasteners, Excellent flow values.

## Ordering information

Filters are also available with bowl guard or metal bowl.

## Item

| Identification | Thread | Flow rate (L/min) | A (mm) | B        | C (mm) |
|----------------|--------|-------------------|--------|----------|--------|
| K- 07 25 06 26 | G 1/4  | 1800              | 48,0   | 155.0 mm | 22,0   |
| K- 07 25 06 28 | G 3/8  | 2000              | 48,0   | 155.0 mm | 22,0   |
| K- 07 25 06 30 | G 1/2  | 3200              | 70,0   | 202.0 mm | 26,0   |
| K- 07 25 06 32 | G 3/4  | 3500              | 70,0   | 202.0 mm | 26,0   |
| K- 07 25 06 34 | G 1    | 3500              | 124,0  | 202.0 mm | 26,0   |

## Spare parts

|                                  |  |
|----------------------------------|--|
| K-ERSATZBEHAELTER VARIOBLOC POLY | Spare tank Polycarbonat                        |
| K-FILTERELEMENT VARIOBLOC        | Filter element                                 |
| K-ABLASSVENTIL AUTO              | Fully-automatic drain valve with Adapter G 1/8 |