


# K-FI MIKRO METALLBEH SICHT VARIOBLO

Micro-filters with metal bowl, incl. sight glass

**HANSA*****FLEX***

## Properties

Input pressure	Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)
Media temperature	max. 50 °C
Ambient temperature	Max. 50 °C (polycarbonate bowl), Max. 80 °C (metal bowl)
Filter rating	0,01 µm
air quality ISO 85731	Class 1 dirt, class 1 oil
Efficiency	99.999 %
Flow rate measurement	At P1 = 7 bar and pressure drop $\Delta p$ = 0,1 bar



## Note

Further information on request

## Description

Borosilicate filter for all applications where compliance with strict compressed air purity requirements is vital. As the second stage downstream of the standard filter, the micro-filter removes 99.999 % of even the finest remaining particles from water, oil and dirt with practically zero residues (filter rating: 0.01 µm).

## Ordering information

Micro-filters are also available with bowl guard or metal bowl.

Item	Identification	Thread	Flow rate (L/min)	A (mm)	B	C (mm)
	K- 07 25 10 90	G 1/4	370	48,0	155.0 mm	22,0
	K- 07 25 10 92	G 3/8	420	48,0	155.0 mm	22,0
	K- 07 25 10 94	G 1/2	1000	70,0	202.0 mm	26,0
	K- 07 25 10 96	G 3/4	1100	70,0	202.0 mm	26,0
	K- 07 25 10 98	G 1	1100	124,0	202.0 mm	26,0

## Spare parts

K-ERSATZBEHAELTER VARIOBLOC POLY	Spare tank Polycarbonat
K-FILTERELEMENT VARIOBLOC	Filter element
K-ABLASSVENTIL AUTO	Fully-automatic drain valve with Adapter G 1/8