



# K-SCHALTVENTILE 3/2 VAROBLOC

On-off valves (3/2-way valves)



### Properties

Protection IP	IP 65 acc. to DIN 40050
Working pressure	3 to 10 bar
Flow rate measurement	At P1 = 6 bar and pressure drop $\Delta p = 1$ bar



### Note

Further information on request

### Description

For pressurising and relieving pneumatic systems. Ideal as the main "on" valve for service units. The pressure in the line is exhausted when the valve is switched off.

Item							
Identification	Thread	Flow rate (L/min)	A (mm)	Connection	B	C (mm)	Voltage
K- 07 25 11 94	G 1/4	2200	48,0	Device plug PG 9, type B, EN 175301-803	147.0 mm	108,0	24 V DC
K- 07 25 11 95	G 3/8	2600	48,0	Device plug PG 9, type B, EN 175301-803	147.0 mm	108,0	24 V DC
K- 07 25 11 96	G 1/2	3300	70,0	Device plug PG 9, type B, EN 175301-803	157.0 mm	113,0	24 V DC
K- 07 25 11 97	G 3/4	3800	70,0	Device plug PG 9, type B, EN 175301-803	157.0 mm	113,0	24 V DC
K- 07 25 11 98	G 1	3800	124,0	Device plug PG 9, type B, EN 175301-803	157.0 mm	113,0	24 V DC

### Spare parts

K-MAGNETSPULE VARIOBLOC	Solenoid
K-GERAETESTECKER	Coupling socket