
K-DRV ABLD SCHNVERSCHR C RAENDEL

Unidirectional flow control valves, outgoing air restriction (»C«), quick-lock screw fitting



Properties			
Operating pressure	Max. 10 bar		
Temp. range	0 °C to +70 °C		
Hollow screw, pivot arm, regulating screw	Nickel-plated brass		
Internal parts	Brass with a bare metal surface		
lip seal O-ring	NBR		
Seals (non-detachable)	Polyamide (glass fibre-reinforced)		





Note

Further information on request

Description

For fine regulation of a cylinder piston speed and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder. Compact type of construction, also ideal where space is restricted. On the version with a knurled screw, the set volumetric flow rate can be locked with the hexagon nut to obtain a fixed setting.

Item						
Identification	C (mm)	for hose	Thread	AF	B (mm)	
K- 07 15 04 54	18,0	4 mm / 2,5 mm	M 5	8 mm	38,9	
K- 07 15 04 55	19,0	5 mm / 3 mm	M 5	8 mm	38,9	
K- 07 15 04 56	19,0	6 mm / 4 mm	M 5	8 mm	38,9	
K- 07 15 04 63	25,0	6 mm / 4 mm	G 1/8	14 mm	42,4	
K- 07 15 04 64	25,0	8 mm / 6 mm	G 1/8	14 mm	42,4	
K- 07 15 04 60	26,5	6 mm / 4 mm	G 1/4	17 mm	51,4	
K- 07 15 04 61	27,5	8 mm / 6 mm	G 1/4	17 mm	51,4	
K- 07 15 04 59	28,5	10 mm / 8 mm	G 1/4	17 mm	51,4	