

K-DRV SCHNVERSCHR V RAENDEL

Unidirectional flow control valves, incoming air restriction (»V«), quick-lock screw fitting

HANSA FLEX

Properties

| | |
|---|------------------------------------|
| Operating pressure | Max. 10 bar |
| Temp. range | 0 °C to +70 °C |
| Hollow screw, pivot arm, regulating screw | Nickel-plated brass |
| Internal parts | Brass with a bare metal surface |
| lip seal O-ring | NBR |
| Seals (non-detachable) | Polyamide (glass fibre-reinforced) |



Note

Further information on request

Description

For fine regulation of a cylinder piston speed in the forward and return motion and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder. Compact type of construction, also ideal where space is restricted. On the version with a knurled screw, the set volumetric flow rate can be locked with the hexagon nut to obtain a fixed setting.

| Item | | | | | |
|----------------|-----------|---------------|--------|-------|-----------|
| Identification | C (mm) | for hose | Thread | AF | B (mm) |
| K- 07 15 05 10 | 18,0 | 4 mm / 2,5 mm | M 5 | 8 mm | 38,9 |
| K- 07 15 05 11 | 19,0 | 5 mm / 3 mm | M 5 | 8 mm | 38,9 |
| K- 07 15 05 12 | 19,0 | 6 mm / 4 mm | M 5 | 8 mm | 38,9 |
| K- 07 15 05 18 | 23,0 | 5 mm / 3 mm | G 1/8 | 14 mm | 42,4 |
| K- 07 15 05 19 | 25,0 | 6 mm / 4 mm | G 1/8 | 14 mm | 42,4 |
| K- 07 15 05 20 | 25,0 | 8 mm / 6 mm | G 1/8 | 14 mm | 42,4 |
| K- 07 15 05 15 | 26,5 | 6 mm / 4 mm | G 1/4 | 17 mm | 51,4 |
| K- 07 15 05 16 | 27,5 | 8 mm / 6 mm | G 1/4 | 17 mm | 51,4 |
| K- 07 15 05 14 | 28,5 | 10 mm / 8 mm | G 1/4 | 17 mm | 51,4 |