


# K-DV STECK B RAENDEL

Bidirectional flow control valves, air restriction at both ends (»B«),  
plug-in connector

**HANSA***FLEX*

## Properties

Operating pressure	Max. 10 bar
Temp. range	0 °C to +70 °C
Hollow screw, pivot arm, regulating screw	Nickel-plated brass
Internal parts	Brass with a bare metal surface
lip seal O-ring	NBR
Seals (non-detachable)	Polyamide (glass fibre-reinforced)



## Note

Further information on request

## Description

For regulation of a cylinder piston speed at both ends and control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece for mounting directly. <br>On the version with a knurled screw, the set volumetric flow rate can be locked with the hexagon nut to obtain a fixed setting.

## Item

Identification	C (mm)	for hose	Thread	AF	B (mm)
K-07 15 04 83	18,6	4 mm	M 5	8 mm	38,9
K-07 15 04 87	20,6	4 mm	G 1/8	14 mm	42,0
K-07 15 04 88	22,7	6 mm	G 1/8	14 mm	42,0
K-07 15 04 89	23,7	8 mm	G 1/8	14 mm	42,0
K-07 15 04 85	24,2	6 mm	G 1/4	17 mm	51,0
K-07 15 04 86	24,7	8 mm	G 1/4	17 mm	51,0
K-07 15 04 84	26,8	10 mm	G 1/4	17 mm	51,0