
K-KDR SCHNVERSCHR

Mini pressure regulators, discharge port on thread, quick-lock screw fitting



Properties			
Control range	0 - 8 bar		
Input pressure	Max. 10 bar		
Temp. range	0 °C to +70 °C		
Hollow screw, pivot arm, regulating screw	Nickel-plated brass		
Internal parts	Brass with a bare metal surface		
lip seal O-ring	NBR		
Seals (non-detachable)	Polyamide (glass fibre-reinforced)		





Note

Further information on request

Description

Piston pressure regulator with self-relieving design, hollow bolt and pivoting ring piece. The regulator is screwed directly into the consumer (e.g. cylinder, handling equipment, etc.). The working pressure can thus be adapted to the specific application.

ltem						
Identification	C (mm)	for hose	Thread	AF	B (mm)	
K- 07 25 08 33	16,0	G 1/8 IG	G 1/8	15 mm	56,0	
K- 07 25 08 34	25,0	5 mm / 3 mm	G 1/8	15 mm	56,0	
K- 07 25 08 35	25,0	6 mm / 4 mm	G 1/8	15 mm	56,0	
K- 07 25 08 36	25,0	8 mm / 6 mm	G 1/8	15 mm	56,0	
K- 07 25 08 31	26,5	6 mm / 4 mm	G 1/4	17 mm	63,0	
K- 07 25 08 32	27,5	8 mm / 6 mm	G 1/4	17 mm	63,0	
K- 07 25 08 30	28,5	10 mm / 8 mm	G 1/4	17 mm	63,0	