K-MAGV MINI

Miniature solenoid valves 15 mm

Properties

Media	Filtered, unlubricated compressed air
Pressure range	0 - 7 bar (NC) with silver plate at manual override 0 - 5 bar (NO) with black plate at manual override
Connection	In manifold base
Temp. range	-5 °C to +45 °C
opening time/closing time	10 - 12 ms (depending on pressure)
output coil	2,5 W
Material	Plastic
Sealant	NBR, stainless steel



Note

Further information on request

Description

Directly controlled 3/2-way solenoid valves specially designed for pneumatic applications. These valves are provided with a flange for assembly on an individual base or multiple manifold base. They feature a monostable manual operator. The scope of supply includes two fixing bolts and a flange gasket. The coils can be turned 180°.

Additional information

Important: The scope of supply does not include a connector. Please order separately.

Item

Identification	Function	Voltage	Connection	H (mm)	B (mm)
K- 07 15 14 18	NC	24 V DC	Cable (30 cm)	42,0	15,0
K- 07 15 14 19	NC	24 V DC	for system plug	42,0	15,0
K- 07 15 14 20	NC	12 V DC	Cable (30 cm)	42,0	15,0
K- 07 15 14 21	NC	12 V DC	for system plug	42,0	15,0
K- 07 15 14 22	NO	24 V DC	Cable (30 cm)	42,0	15,0
K- 07 15 14 23	NO	24 V DC	for system plug	42,0	15,0
K- 07 15 14 24	NO	12 V DC	Cable (30 cm)	42,0	15,0
K- 07 15 14 25	NO	12 V DC	for system plug	42,0	15,0

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.