


# K-MAGV MINI

Miniature solenoid valves 15 mm

**HANSA FLEX**

## Properties

<b>Media</b>	Filtered, unlubricated compressed air
<b>Pressure range</b>	0 - 7 bar (NC) with silver plate at manual override 0 - 5 bar (NO) with black plate at manual override
<b>Connection</b>	In manifold base
<b>Temp. range</b>	-5 °C to +45 °C
<b>opening time/closing time</b>	10 - 12 ms (depending on pressure)
<b>output coil</b>	2,5 W
<b>Material</b>	Plastic
<b>Sealant</b>	NBR, stainless steel



## Note

Further information on request

## Description

Directly controlled 3/2-way solenoid valves specially designed for pneumatic applications. These valves are provided with a flange for assembly on an individual base or multiple manifold base. They feature a monostable manual operator. The scope of supply includes two fixing bolts and a flange gasket. The coils can be turned 180°.

## Additional information

Important: The scope of supply does not include a connector. Please order separately.

## Item

Identification	Function	Voltage	Connection	H (mm)	B (mm)
K- 07 15 14 18	NC	24 V DC	Cable (30 cm)	42,0	15,0
K- 07 15 14 19	NC	24 V DC	for system plug	42,0	15,0
K- 07 15 14 20	NC	12 V DC	Cable (30 cm)	42,0	15,0
K- 07 15 14 21	NC	12 V DC	for system plug	42,0	15,0
K- 07 15 14 22	NO	24 V DC	Cable (30 cm)	42,0	15,0
K- 07 15 14 23	NO	24 V DC	for system plug	42,0	15,0
K- 07 15 14 24	NO	12 V DC	Cable (30 cm)	42,0	15,0
K- 07 15 14 25	NO	12 V DC	for system plug	42,0	15,0