K-PNEU LOGIKELEMENTE

Pneumatic logic elements

Properties

Working pressure	OR-AND: 1.5-8 bar, NOT: 0.4-6 bar, YES - MEMORY: 0.0-8 bar (pilot pressure from 1.5-8 bar)
Temp. range	-10 °C to +60 °C
Connection	Push-in fitting for 4 mm pipe
Flow rate	100 l/min (at 6 bar and Δp = 1 bar)
nominal Ø	2,7 mm
Reset	OR - AND: by compressed air, MEMORY: by air, YES - NOT: by mechanical spring
Material	Technopolymer
Slider	Aluminium
Sealant	NBR



Note

Further information on request

Description

Pneumatic logic elements are available with five different functions: OR, AND, NOT, YES, MEMORY. All elements have an adapter for the Ω-rail (DIN EN 50022) integral with the body.

Item

Identification	Function	Height (mm)	Length (mm)
K- 07 15 13 77	OR	40	38,5
K- 07 15 13 78	AND	40	38,5
K- 07 15 13 79	NOT	40	55,2
K- 07 15 13 80	YES	40	55,2
K- 07 15 13 81	MEMORY	41	89,5

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.