


K-RUNDZYLINDER DOPP O D 1

Round cylinders, double acting (magnetic, non-cushioned)



Properties

Media	Filtered (50 µm), unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.
Working pressure	Max. 10 bar
Set pressure	0,4 bar (Ø 32 und Ø 40), 0,3 bar (Ø 50)
Temp. range	-10 °C to +80 °C
Design	Screwed joint between stainless steel barrel and heads
Piston rod	C45 steel, hard chrome-plated
Pipe	Anodised aluminium
Piston	Technopolymer
Sealant	NBR



Note

Further information on request

Description

Version with magnetic piston

Ordering information

Note: 500 mm is the maximum stroke available for the double-acting type.

Additional information

Important: The scope of supply does not include a connector. Please order separately.

Note: 500 mm is the maximum stroke available for the double-acting type.

Item	Identification	Ø piston	Stroke (mm)	Connection	Thread piston rod
	K- 07 15 17 29	32 mm	25	G 1/8	M 10 x 1.25
	K- 07 15 17 30	32 mm	50	G 1/8	M 10 x 1.25
	K- 07 15 17 31	32 mm	80	G 1/8	M 10 x 1.25
	K- 07 15 17 32	32 mm	100	G 1/8	M 10 x 1.25
	K- 07 15 17 33	32 mm	125	G 1/8	M 10 x 1.25
	K- 07 15 17 34	32 mm	160	G 1/8	M 10 x 1.25
	K- 07 15 17 35	32 mm	200	G 1/8	M 10 x 1.25
	K- 07 15 17 36	32 mm	250	G 1/8	M 10 x 1.25
	K- 07 15 17 37	32 mm	320	G 1/8	M 10 x 1.25
	K- 07 15 17 38	32 mm	400	G 1/8	M 10 x 1.25
	K- 07 15 17 39	32 mm	500	G 1/8	M 10 x 1.25
	K- 07 15 17 40	40 mm	25	G 1/4	M 12 x 1.25
	K- 07 15 17 41	40 mm	50	G 1/4	M 12 x 1.25
	K- 07 15 17 42	40 mm	80	G 1/4	M 12 x 1.25
	K- 07 15 17 43	40 mm	100	G 1/4	M 12 x 1.25
	K- 07 15 17 44	40 mm	125	G 1/4	M 12 x 1.25
	K- 07 15 17 45	40 mm	160	G 1/4	M 12 x 1.25
	K- 07 15 17 46	40 mm	200	G 1/4	M 12 x 1.25
	K- 07 15 17 47	40 mm	250	G 1/4	M 12 x 1.25
	K- 07 15 17 48	40 mm	320	G 1/4	M 12 x 1.25
	K- 07 15 17 49	40 mm	400	G 1/4	M 12 x 1.25
	K- 07 15 17 50	40 mm	500	G 1/4	M 12 x 1.25
	K- 07 15 17 51	50 mm	25	G 1/4	M 16 x 1.5
	K- 07 15 17 52	50 mm	50	G 1/4	M 16 x 1.5
	K- 07 15 17 53	50 mm	80	G 1/4	M 16 x 1.5
	K- 07 15 17 54	50 mm	100	G 1/4	M 16 x 1.5
	K- 07 15 17 55	50 mm	125	G 1/4	M 16 x 1.5
	K- 07 15 17 56	50 mm	160	G 1/4	M 16 x 1.5
	K- 07 15 17 57	50 mm	200	G 1/4	M 16 x 1.5
	K- 07 15 17 58	50 mm	250	G 1/4	M 16 x 1.5



K-RUNDZYLINDER DOPP O D 1

Round cylinders, double acting (magnetic, non-cushioned)

Item				
Identification	Ø piston	Stroke (mm)	Connection	Thread piston rod
K- 07 15 17 59	50 mm	320	G 1/4	M 16 x 1.5
K- 07 15 17 60	50 mm	400	G 1/4	M 16 x 1.5
K- 07 15 17 61	50 mm	500	G 1/4	M 16 x 1.5

Accessories	
K-FUSSBEFESTIGUNG 2	Foot model
K-KOPFMUTTER DECKEL BODEN	Hexagon nut (for head)
K-GABELKOEPF 4	Fork model
K-GELENKAUGEN 5	Rod eye model
K-SCHWENKLAGER 2	Counter-hinge model
K-SENSORHALTER	Sensor support (with T-slot adapter)
K-SENSOREN T-NUT 1	Sensor for T-slot