

K-WV 3/2 ELEKTROPNEUMATISCH

3/2-way pilot valves

HANSA FLEX

Properties

| | |
|---------------------------------|--|
| Operating pressure | 2,5 - 10 bar (monostable)\n1,0 - 10 bar (bistable)\nvacuum up to 10 bar (external pilot air) |
| min. working pressure | 2.5 bar (monostable), 1.0 bar (bistable) |
| Temp. range | -10 °C to +60 °C |
| Flow rate 6bar and 10bar | 550 NI/min (G 1/8), 1100 NI/min (G 1/4), 2150 NI/min (G 3/8), 4600 NI/min (G 1/2) |
| Flow rate 6bar and 5bar | 400 NI/min (G 1/8), 750 NI/min (G 1/4), 1560 NI/min (G 3/8), 3200 NI/min (G 1/2) |



Note

Further information on request

Item

| Identification | Connection | Voltage | DN | Function | circuit diagram number | Control |
|----------------|------------|--------------|----|------------|------------------------|---------|
| K- 07 15 00 23 | G 1/8 | 24 V DC | 5 | 3/-way NO | 32 | |
| K- 07 15 00 24 | G 1/4 | 24 V DC | 8 | 3/-way NO | 32 | |
| K- 07 15 25 75 | G 3/8 | 24 V DC | 13 | 3/-way NO | 32 | |
| K- 07 15 00 25 | G 1/2" | 24 V DC | 15 | 3/-way NO | 32 | |
| K- 07 15 00 26 | G 1/8 | 230 V, 50 Hz | 5 | 3/-way NO | 32 | |
| K- 07 15 00 27 | G 1/4 | 230 V, 50 Hz | 8 | 3/-way NO | 32 | |
| K- 07 15 25 76 | G 3/8 | 230 V, 50 Hz | 13 | 3/-way NO | 32 | |
| K- 07 15 00 28 | G 1/2" | 230 V, 50 Hz | 15 | 3/-way NO | 32 | |
| K- 07 15 00 29 | G 1/8 | 24 V DC | 5 | 3/2-way NC | 33 | |
| K- 07 15 00 30 | G 1/4 | 24 V DC | 8 | 3/2-way NC | 33 | |
| K- 07 15 25 77 | G 3/8 | 24 V DC | 13 | 3/2-way NC | 33 | |
| K- 07 15 00 31 | G 1/2" | 24 V DC | 15 | 3/2-way NC | 33 | |
| K- 07 15 00 32 | G 1/8 | 230 V, 50 Hz | 5 | 3/2-way NC | 33 | |
| K- 07 15 00 33 | G 1/4 | 230 V, 50 Hz | 8 | 3/2-way NC | 33 | |
| K- 07 15 25 78 | G 3/8 | 230 V, 50 Hz | 13 | 3/2-way NC | 33 | |
| K- 07 15 00 34 | G 1/2" | 230 V, 50 Hz | 15 | 3/2-way NC | 33 | |
| K- 07 15 00 35 | G 1/8 | 24 V DC | 5 | 3/2-way | 34 | |
| K- 07 15 00 36 | G 1/4 | 24 V DC | 8 | 3/2-way | 34 | |
| K- 07 15 25 79 | G 3/8 | 24 V DC | 13 | 3/2-way | 34 | |
| K- 07 15 00 37 | G 1/2" | 24 V DC | 15 | 3/2-way | 34 | |
| K- 07 15 00 38 | G 1/8 | 230 V, 50 Hz | 5 | 3/2-way | 34 | |
| K- 07 15 00 39 | G 1/4 | 230 V, 50 Hz | 8 | 3/2-way | 34 | |
| K- 07 15 25 80 | G 3/8 | 230 V, 50 Hz | 13 | 3/2-way | 34 | |
| K- 07 15 00 40 | G 1/2" | 230 V, 50 Hz | 15 | 3/2-way | 34 | |