

# K-WV 5/2 ELEKTROPNEUMATISCH

5/2-way pilot valves

**HANSA FLEX**

## Properties

|                                 |  |
|---------------------------------|--|
| <b>Operating pressure</b>       | 2,5 - 10 bar (monostable)\n1,0 - 10 bar (bistable)\nvacuum up to 10 bar (external pilot air) |
| <b>min. working pressure</b>    | 2.5 bar (monostable), 1.0 bar (bistable)   |
| <b>Temp. range</b>              | -10 °C to +60 °C   |
| <b>Flow rate 6bar and 10bar</b> | 550 NI/min (G 1/8), 1100 NI/min (G 1/4), 2150 NI/min (G 3/8), 4600 NI/min (G 1/2)            |
| <b>Flow rate 6bar and 5bar</b>  | 400 NI/min (G 1/8), 750 NI/min (G 1/4), 1560 NI/min (G 3/8), 3200 NI/min (G 1/2)             |



## Note

Further information on request

## Item

| Identification | Connection | Voltage      | DN | Function | circuit diagram number | Control |
|----------------|------------|--------------|----|----------|------------------------|---------|
| K- 07 15 01 93 | G 1/8      | 24 V DC      | 5  | 5/2-way  | 35                     |         |
| K- 07 15 01 94 | G 1/4      | 24 V DC      | 8  | 5/2-way  | 35                     |         |
| K- 07 15 25 81 | G 3/8      | 24 V DC      | 13 | 5/2-way  | 35                     |         |
| K- 07 15 01 95 | G 1/2"     | 24 V DC      | 15 | 5/2-way  | 35                     |         |
| K- 07 15 01 96 | G 1/8      | 230 V, 50 Hz | 5  | 5/2-way  | 35                     |         |
| K- 07 15 01 97 | G 1/4      | 230 V, 50 Hz | 8  | 5/2-way  | 35                     |         |
| K- 07 15 25 82 | G 3/8      | 230 V, 50 Hz | 13 | 5/2-way  | 35                     |         |
| K- 07 15 01 98 | G 1/2"     | 230 V, 50 Hz | 15 | 5/2-way  | 35                     |         |
| K- 07 15 01 99 | G 1/8      | 24 V DC      | 5  | 5/2-way  | 36                     |         |
| K- 07 15 02 00 | G 1/4      | 24 V DC      | 8  | 5/2-way  | 36                     |         |
| K- 07 15 25 83 | G 3/8      | 24 V DC      | 13 | 5/2-way  | 36                     |         |
| K- 07 15 02 01 | G 1/2"     | 24 V DC      | 15 | 5/2-way  | 36                     |         |
| K- 07 15 02 02 | G 1/8      | 230 V, 50 Hz | 5  | 5/2-way  | 36                     |         |
| K- 07 15 02 03 | G 1/4      | 230 V, 50 Hz | 8  | 5/2-way  | 36                     |         |
| K- 07 15 25 84 | G 3/8      | 230 V, 50 Hz | 13 | 5/2-way  | 36                     |         |
| K- 07 15 02 04 | G 1/2"     | 230 V, 50 Hz | 15 | 5/2-way  | 36                     |         |