K-WV 3/2 5/2 5/3 HAND

3/2, 5/2 and 5/3-way pilot valves

Properties

Operating pressure	2.5 - 10 bar (monostable)\n1.0 - 10 bar (bistable)\nMax. vacuum 10 bar
Temp. range	-10 °C to +60 °C
Flow rate 6bar and 10bar	550 Nl/min (G 1/8), 1100 Nl/min (G 1/4), 2150 Nl/min (G 3/8), 4600 Nl/min (G 1/2)
Flow rate 6bar and 5bar	400 Nl/min (G 1/8), 750 Nl/min (G 1/4), 1560 Nl/min (G 3/8), 3200 Nl/min (G 1/2)
Valve body	Aluminium
Spring	Special steel
Piston	Nickel-plated aluminium
Sealant	NBR



Note

Further information on request

Item

Identification	Connection	Function	circuit diagram number	Control
K- 07 15 00 70	G 1/8	3/2-way	10	
K- 07 15 00 71	G 1/8	3/2-way	11	
K- 07 15 00 72	G 1/4	3/2-way	10	
K- 07 15 00 73	G 1/4	3/2-way	11	
K- 07 15 00 74	G 1/2"	3/2-way	10	
K- 07 15 00 75	G 1/2"	3/2-way	11	
K- 07 15 02 29	G 1/8	5/2-way	12	
K- 07 15 02 30	G 1/8	5/2-way	13	
K- 07 15 02 31	G 1/4	5/2-way	12	
K- 07 15 02 32	G 1/4	5/2-way	13	
K- 07 15 02 33	G 1/2"	5/2-way	12	
K- 07 15 02 34	G 1/2"	5/2-way	13	
K- 07 15 03 57	G 1/8	5/3-way	14	
K- 07 15 03 58	G 1/8	5/3-way	15	
K- 07 15 03 59	G 1/8	5/3-way	16	
K- 07 15 03 60	G 1/8	5/3-way	17	-
K- 07 15 03 61	G 1/8	5/3-way	18	-
K- 07 15 03 62	G 1/8	5/3-way	19	-
K- 07 15 03 63	G 1/4	5/3-way	14	
K- 07 15 03 64	G 1/4	5/3-way	15	
K- 07 15 03 65	G 1/4	5/3-way	16	
K- 07 15 03 66	G 1/4	5/3-way	17	-
K- 07 15 03 67	G 1/4	5/3-way	18	-
K- 07 15 03 68	G 1/4	5/3-way	19	-
K- 07 15 03 69	G 1/2"	5/3-way	14	
K- 07 15 03 70	G 1/2"	5/3-way	15	
K- 07 15 03 71	G 1/2"	5/3-way	16	
K- 07 15 03 72	G 1/2"	5/3-way	17	-
K- 07 15 03 73	G 1/2"	5/3-way	18	-
K- 07 15 03 74	G 1/2"	5/3-way	19	-

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.