

# K-WV 3/2 MANU K DREHHEBEL

3/2-way pilot valves, manually operated, with short wing lever, NC

**HANSA FLEX**

## Properties

|                                 |   |
|---------------------------------|---|
| <b>Operating pressure</b>       | 2.5 - 10 bar (monostable)\n1.0 - 10 bar (bistable)\nMax. vacuum 10 bar (external pilot air) |
| <b>Temp. range</b>              | -10 °C to +60 °C  |
| <b>Flow rate 6bar and 10bar</b> | 550 NI/min  |
| <b>Flow rate 6bar and 5bar</b>  | 400 NI/min  |
| <b>Valve body</b>               | Aluminium   |
| <b>Spring</b>                   | Special steel   |
| <b>Piston</b>                   | Aluminium   |
| <b>Sealant</b>                  | NBR   |



## Note

3 valve positions only in conjunction with a second 3/2-way valve. <br>Corresponds to a 5/3-way valve.  
Further information on request

## Additional information

Important: The scope of supply does not include a connector. Please order separately.

| Item           |            |        |            |                  |
|----------------|------------|--------|------------|------------------|
| Identification | Connection | Symbol | Operation  | switch positions |
| K- 07 15 00 78 | G 1/8      | 5      | monostable | 2                |
| K- 07 15 00 79 | G 1/8      | 6      | bistable   | 2                |
| K- 07 15 00 80 | G 1/8      | 7      | monostable | 3*               |
| K- 07 15 00 81 | G 1/8      | 8      | bistable   | 3*               |