

K-WV 3/2 MANU K DREHHEBEL

3/2-way pilot valves, manually operated, with short wing lever, NC



| Properties | |
|--------------------------|---|
| Operating pressure | 2.5 - 10 bar (monostable)\n1.0 - 10 bar (bistable)\nMax. vacuum 10 bar (external pilot air) |
| Temp. range | -10 °C to +60 °C |
| Flow rate 6bar and 10bar | 550 NI/min |
| Flow rate 6bar and 5bar | 400 NI/min |
| Valve body | Aluminium |
| Spring | Special steel |
| Piston | Aluminium |
| Sealant | NBR |



Note
3 valve positions only in conjunction with a second 3/2-way valve.
Corresponds to a 5/3-way valve.
Further information on request

Additional information
Important: The scope of supply does not include a connector. Please order separately.

| Item | | | | |
|----------------|------------|--------|------------|------------------|
| Identification | Connection | Symbol | Operation | switch positions |
| K- 07 15 00 78 | G 1/8 | 5 | monostable | 2 |
| K- 07 15 00 79 | G 1/8 | 6 | bistable | 2 |
| K- 07 15 00 80 | G 1/8 | 7 | monostable | 3* |
| K- 07 15 00 81 | G 1/8 | 8 | bistable | 3* |