# K-WV 3/2 MANU L DREHHEBEL

3/2-way pilot valves, manually operated, with long wing lever, NC

## Properties

| | |
|---|---|
| **Operating pressure** | 2.5 - 10 bar (monostable)\n1.0 - 10 bar (bistable)\nMax. vacuum 10 bar (external pilot air) |
| **Temp. range** | -10 °C to +60 °C |
| **Flow rate 6bar and 10bar** | 550 Nl/min |
| **Flow rate 6bar and 5bar** | 400 Nl/min |
| **Valve body** | Aluminium |
| **Spring** | Special steel |
| **Piston** | Aluminium |
| **Sealant** | NBR |



## Note

3 valve positions only in conjunction with a second 3/2-way valve. <br>Corresponds to a 5/3-way valve.
Further information on request

## Additional information

Important: The scope of supply does not include a connector. Please order separately.

## Item

| Identification | Connection | Symbol | Operation | switch positions |
|---|---|---|---|---|
| **K- 07 15 00 82** | G 1/8 | 9 | monostable | 2 |
| **K- 07 15 00 83** | G 1/8 | 10 | bistable | 2 |
| **K- 07 15 00 84** | G 1/8 | 11 | monostable | 3* |
| **K- 07 15 00 85** | G 1/8 | 12 | bistable | 3* |

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*