

# K-WV 3/2 MANU PILZTAST

3/2-way pilot valve, manually operated, with mushroom pushbutton, NC

**HANSA FLEX**

## Properties

|                                 |   |
|---------------------------------|---|
| <b>Operating pressure</b>       | 2.5 - 10 bar (monostable)\n1.0 - 10 bar (bistable)\nMax. vacuum 10 bar (external pilot air) |
| <b>Temp. range</b>              | -10 °C to +60 °C  |
| <b>Flow rate 6bar and 10bar</b> | 550 NI/min  |
| <b>Flow rate 6bar and 5bar</b>  | 400 NI/min  |
| <b>Operation</b>                | Monostable  |
| <b>Valve body</b>               | Aluminium   |
| <b>Spring</b>                   | Special steel   |
| <b>Piston</b>                   | Aluminium   |
| <b>Sealant</b>                  | NBR   |



## Note

3 valve positions only in conjunction with a second 3/2-way valve. <br>Corresponds to a 5/3-way valve.  
Further information on request

## Additional information

Important: The scope of supply does not include a connector. Please order separately.

## Item

| Identification | Connection | Symbol | Operation  |
|----------------|------------|--------|------------|
| K- 07 15 00 86 | G 1/8      | 13     | monostable |