


K-WV 3/2 PNEUMATISCH

3/2-way pilot valves

HANSA FLEX

Properties

Operating pressure	Max. vacuum 10 bar
min. working pressure	2.5 bar (monostable), 1.0 bar (bistable)
Temp. range	-10 °C to +60 °C
Flow rate 6bar and 10bar	550 NI/min (G 1/8), 1100 NI/min (G 1/4), 2150 NI/min (G 3/8), 4600 NI/min (G 1/2)
Flow rate 6bar and 5bar	400 NI/min (G 1/8), 750 NI/min (G 1/4), 1560 NI/min (G 3/8), 3200 NI/min (G 1/2)
Pilot air connection	G 1/8



Note

Further information on request

Item

Identification	Connection	DN	Function	circuit diagram number	Control
K- 07 15 00 41	G 1/8	5	3/-way NO	24	
K- 07 15 00 42	G 1/4	8	3/-way NO	24	
K- 07 15 00 45	G 1/2"	15	3/-way NO	24	
K- 07 15 25 67	G 3/8	13	3/-way NO	24	
K- 07 15 00 43	G 1/8	5	3/2-way NC	25	
K- 07 15 00 44	G 1/4	8	3/2-way NC	25	
K- 07 15 00 46	G 1/2"	15	3/2-way NC	25	
K- 07 15 25 68	G 3/8	13	3/2-way NC	25	
K- 07 15 00 47	G 1/8	5	3/2-way	26	
K- 07 15 00 48	G 1/4	8	3/2-way	26	
K- 07 15 00 49	G 1/2"	15	3/2-way	26	
K- 07 15 25 69	G 3/8	13	3/2-way	26	