

# K-WV 3/2 PNEUMATISCH

3/2-way pilot valves

**HANSA FLEX**

## Properties

<b>Operating pressure</b>	Max. vacuum 10 bar
<b>min. working pressure</b>	2.5 bar (monostable), 1.0 bar (bistable)
<b>Temp. range</b>	-10 °C to +60 °C
<b>Flow rate 6bar and 10bar</b>	550 NI/min (G 1/8), 1100 NI/min (G 1/4), 2150 NI/min (G 3/8), 4600 NI/min (G 1/2)
<b>Flow rate 6bar and 5bar</b>	400 NI/min (G 1/8), 750 NI/min (G 1/4), 1560 NI/min (G 3/8), 3200 NI/min (G 1/2)
<b>Pilot air connection</b>	G 1/8



## Note

Further information on request

## Item

Identification	Connection	DN	Function	circuit diagram number	Control
K- 07 15 00 41	G 1/8	5	3/-way NO	24	
K- 07 15 00 42	G 1/4	8	3/-way NO	24	
K- 07 15 00 45	G 1/2"	15	3/-way NO	24	
K- 07 15 25 67	G 3/8	13	3/-way NO	24	
K- 07 15 00 43	G 1/8	5	3/2-way NC	25	
K- 07 15 00 44	G 1/4	8	3/2-way NC	25	
K- 07 15 00 46	G 1/2"	15	3/2-way NC	25	
K- 07 15 25 68	G 3/8	13	3/2-way NC	25	
K- 07 15 00 47	G 1/8	5	3/2-way	26	
K- 07 15 00 48	G 1/4	8	3/2-way	26	
K- 07 15 00 49	G 1/2"	15	3/2-way	26	
K- 07 15 25 69	G 3/8	13	3/2-way	26	