

# K-WV 5/2 PNEUMATISCH

5/2-way pilot valves

**HANSA FLEX**

## Properties

<b>Operating pressure</b>	Max. vacuum 10 bar
<b>min. working pressure</b>	2.5 bar (monostable), 1.0 bar (bistable)
<b>Temp. range</b>	-10 °C to +60 °C
<b>Flow rate 6bar and 10bar</b>	550 NI/min (G 1/8), 1100 NI/min (G 1/4), 2150 NI/min (G 3/8), 4600 NI/min (G 1/2)
<b>Flow rate 6bar and 5bar</b>	400 NI/min (G 1/8), 750 NI/min (G 1/4), 1560 NI/min (G 3/8), 3200 NI/min (G 1/2)
<b>Pilot air connection</b>	G 1/8



## Note

Further information on request

## Item

Identification	Connection	DN	Function	circuit diagram number	Control
K- 07 15 02 11	G 1/8	5	5/2-way	27	
K- 07 15 02 12	G 1/4	8	5/2-way	27	
K- 07 15 25 70	G 3/8	13	5/2-way	27	
K- 07 15 02 15	G 1/2"	15	5/2-way	27	
K- 07 15 02 13	G 1/8	5	5/2-way	28	
K- 07 15 02 14	G 1/4	8	5/2-way	28	
K- 07 15 25 71	G 3/8	13	5/2-way	28	
K- 07 15 02 16	G 1/2"	15	5/2-way	28	