
K-WV 5/2 PNEUMATISCH

5/2-way pilot valves

Properties

Operating pressure	Max. vacuum 10 bar
min. working pressure	2.5 bar (monostable), 1.0 bar (bistable)
Temp. range	-10 °C to +60 °C
Flow rate 6bar and 10bar	550 Nl/min (G 1/8), 1100 Nl/min (G 1/4), 2150 Nl/min (G 3/8), 4600 Nl/min (G 1/2)
Flow rate 6bar and 5bar	400 Nl/min (G 1/8), 750 Nl/min (G 1/4), 1560 Nl/min (G 3/8), 3200 Nl/min (G 1/2)
Pilot air connection	G 1/8



Note

Further information on request

Item

Identification	Connection	DN	Function	circuit diagram number	Control
K- 07 15 02 11	G 1/8	5	5/2-way	27	
K- 07 15 02 12	G 1/4	8	5/2-way	27	
K- 07 15 25 70	G 3/8	13	5/2-way	27	
K- 07 15 02 15	G 1/2"	15	5/2-way	27	
K- 07 15 02 13	G 1/8	5	5/2-way	28	
K- 07 15 02 14	G 1/4	8	5/2-way	28	
K- 07 15 25 71	G 3/8	13	5/2-way	28	
K- 07 15 02 16	G 1/2"	15	5/2-way	28	

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.