


K-WV 5/3 MITTELSTELLUNSVENT

5/3-way pilot valves (monostable)

HANSA FLEX

Properties

Operating principle	5/3-way
Operating pressure	Max. vacuum 10 bar
min. working pressure	
Temp. range	-10 °C to +60 °C
Flow rate 6bar and 10bar	550 NI/min (G 1/8), 1100 NI/min (G 1/4), 2150 NI/min (G 3/8), 4600 NI/min (G 1/2)
Flow rate 6bar and 5bar	400 NI/min (G 1/8), 750 NI/min (G 1/4), 1560 NI/min (G 3/8), 3200 NI/min (G 1/2)



Note

Further information on request

Item

Identification	Connection	DN	Function	circuit diagram number
K- 07 15 03 48	G 1/8	5	5/3-way	29
K- 07 15 03 49	G 1/8	5	5/3-way	30
K- 07 15 03 50	G 1/8	5	5/3-way	31
K- 07 15 03 51	G 1/4	8	5/3-way	29
K- 07 15 03 52	G 1/4	8	5/3-way	30
K- 07 15 03 53	G 1/4	8	5/3-way	31
K- 07 15 25 72	G 3/8	13	5/3-way	29
K- 07 15 25 73	G 3/8	13	5/3-way	30
K- 07 15 25 74	G 3/8	13	5/3-way	31
K- 07 15 03 54	G 1/2"	15	5/3-way	29
K- 07 15 03 55	G 1/2"	15	5/3-way	30
K- 07 15 03 56	G 1/2"	15	5/3-way	31