


# K-VORFILTER METALLBEHAEL MULTIFIX

Pre-filters with metal bowl

**HANSA FLEX**

## Properties

<b>Input pressure</b>	Max. 16 bar
<b>Media temperature</b>	max. 60 °C
<b>Ambient temperature</b>	Max. 60 °C
<b>Filter rating</b>	0,30 µm
<b>Efficiency</b>	99.999 %
<b>Sealant</b>	NBR
<b>Filter insert</b>	Paper-POM
<b>Housing</b>	Die-cast zinc
<b>Drain valve</b>	Semi-automatic
<b>Flow rate measurement</b>	FV at P1 = 6 bar and $\Delta p = 0.02$ bar



## Note

\* = Dimensions with adapter plate!  
Further information on request

## Description

Micro-filters for compliance with strict compressed air purity requirements. Suitable for all applications where standard filters do not afford the desired efficiency.

## Additional information

on Art. K-07250721: Max. inlet pressure 300 bar. Other cylinder pressure regulators available on request.

## Item

Identification	Thread	Flow rate (L/min)	A (mm)	B	C (mm)	D (mm)	DN
K- 07 25 10 69	G 1/4	160	47,8	152.5 mm	27,0	125,5	6
K- 07 25 10 72	G 1/2	500	68,8	182.7 mm (187.7 mm)*	72,0	149,2	15

## Spare parts

K-HALTERBAUSATZ MULTIFIX	Holder
K-KOPPELPAKET MEHR	Coupling packet
K-KOPPELPAKET SCHMA	Coupling packet
K-AUTOMAT ABLASSVENTIL	Automatic drain valve
K-PC-BEHAELTER FILTER MULTIFIX	Polycarbonate tank filter
K-METALLBEHAELTER OELER MULTIFIX	Metal tank oiler