

# K-FI MIKRO PC-BEHÄEL SCHU MULTIFIX

Micro-filters with polycarbonate bowl and bowl guard

**HANSA FLEX**

## Properties

<b>Input pressure</b>	Max. 16 bar
<b>Media temperature</b>	max. 60 °C
<b>Ambient temperature</b>	Max. 60 °C
<b>Filter rating</b>	0,01 µm
<b>Efficiency</b>	99.999 %
<b>Sealant</b>	NBR
<b>Filter insert</b>	Borosilicate-POM
<b>Housing</b>	Die-cast zinc
<b>Drain valve</b>	Semi-automatic
<b>Flow rate measurement</b>	FM at P1 = 6 bar and $\Delta p = 0.09$ bar



## Note

\* = Dimensions with adapter plate!  
Further information on request

## Description

Micro-filters for compliance with strict compressed air purity requirements. Suitable for all applications where standard filters do not afford the desired efficiency.

## Additional information

on Art. K-07250721: Max. inlet pressure 300 bar. Other cylinder pressure regulators available on request.

## Item

Identification	Thread	Flow rate (L/min)	A (mm)	B	C (mm)	D (mm)	DN	Size
K- 07 25 10 60	G 1/4	280	47,8	152.1 mm	27,0	125,1	6	1
K- 07 25 10 63	G 1/2	720	68,8	180.8 mm (185.8 mm)*	72,0	147,3	15	2

## Spare parts

K-HALTERBAUSATZ MULTIFIX	Holder
K-KOPPELPAKET MEHR	Coupling packet
K-KOPPELPAKET SCHMA	Coupling packet
K-AUTOMAT ABLASSVENTIL	Automatic drain valve
K-PC-BEHÄELTER FILTER MULTIFIX	Polycarbonate tank filter
K-METALLBEHÄELTER OELER MULTIFIX	Metal tank oiler