

K-FI MIKRO PC-BEHÄLTER SCHU MULTIFIX

Micro-filters with polycarbonate bowl and bowl guard

HANSA FLEX

Properties

| | |
|-----------------------|--|
| Input pressure | Max. 16 bar |
| Media temperature | max. 60 °C |
| Ambient temperature | Max. 60 °C |
| Filter rating | 0,01 µm |
| Efficiency | 99.999 % |
| Sealant | NBR |
| Filter insert | Borosilicate-POM |
| Housing | Die-cast zinc |
| Drain valve | Semi-automatic |
| Flow rate measurement | FM at P1 = 6 bar and $\Delta p = 0.09$ bar |



Note

* = Dimensions with adapter plate!
Further information on request

Description

Micro-filters for compliance with strict compressed air purity requirements. Suitable for all applications where standard filters do not afford the desired efficiency.

Additional information

on Art. K-07250721: Max. inlet pressure 300 bar. Other cylinder pressure regulators available on request.

Item

| Identification | Thread | Flow rate (L/min) | A (mm) | B | C (mm) | D (mm) | DN | Size |
|----------------|--------|----------------------|-----------|----------------------|-----------|-----------|----|------|
| K- 07 25 10 60 | G 1/4 | 280 | 47,8 | 152.1 mm | 27,0 | 125,1 | 6 | 1 |
| K- 07 25 10 63 | G 1/2 | 720 | 68,8 | 180.8 mm (185.8 mm)* | 72,0 | 147,3 | 15 | 2 |

Spare parts

| | |
|---------------------------------|---------------------------|
| K-HALTERBAUSATZ MULTIFIX | Holder |
| K-KOPPELPAKET MEHR | Coupling packet |
| K-KOPPELPAKET SCHMA | Coupling packet |
| K-AUTOMAT ABLASSVENTIL | Automatic drain valve |
| K-PC-BEHÄLTER FILTER MULTIFIX | Polycarbonate tank filter |
| K-METALLBEHÄLTER OELER MULTIFIX | Metal tank oiler |