

K-FI AK KOH METALLBEHAEL MULTIFIX

Activated carbon filters with metal bowl

HANSA FLEX

Properties

| | |
|------------------------------|---|
| Input pressure | Max. 16 bar |
| Media temperature | max. 60 °C |
| Ambient temperature | Max. 60 °C |
| Sealant | NBR |
| Filter insert | Activated carbon-POM |
| Housing | Die-cast zinc |
| Drain valve | Semi-automatic |
| Residual oil content | 0.005 mg/m ³ |
| Flow rate measurement | FA at P1 = 6 bar and $\Delta p = 0.2$ bar |



Note

Further information on request

Description

Micro-filters for compliance with strict compressed air purity requirements. Suitable for all applications where standard filters do not afford the desired efficiency.

| Item | | | | | | | | |
|----------------|--------|-------------------|--------|----------|--------|--------|----|------|
| Identification | Thread | Flow rate (L/min) | A (mm) | B | C (mm) | D (mm) | DN | Size |
| K- 07 25 10 49 | G 1/4 | 380 | 47,8 | 137.0 mm | 27,0 | 110,0 | 6 | 1 |
| K- 07 25 10 52 | G 1/2 | 1500 | 68,8 | 168.2 mm | 34,5 | 133,7 | 15 | 2 |

Spare parts

| | |
|----------------------------------|---------------------------|
| K-HALTERBAUSATZ MULTIFIX | Holder |
| K-KOPPELPAKET MEHR | Coupling packet |
| K-KOPPELPAKET SCHMA | Coupling packet |
| K-PC-BEHAELTER FILTER MULTIFIX | Polycarbonate tank filter |
| K-METALLBEHAELTER OELER MULTIFIX | Metal tank oiler |