

# K-FI AK KOH METALLBEHAEL MULTIFIX

Activated carbon filters with metal bowl

**HANSA FLEX**

## Properties

<b>Input pressure</b>	Max. 16 bar
<b>Media temperature</b>	max. 60 °C
<b>Ambient temperature</b>	Max. 60 °C
<b>Sealant</b>	NBR
<b>Filter insert</b>	Activated carbon-POM
<b>Housing</b>	Die-cast zinc
<b>Drain valve</b>	Semi-automatic
<b>Residual oil content</b>	0.005 mg/m <sup>3</sup>
<b>Flow rate measurement</b>	FA at P1 = 6 bar and $\Delta p = 0.2$ bar



## Note

Further information on request

## Description

Micro-filters for compliance with strict compressed air purity requirements. Suitable for all applications where standard filters do not afford the desired efficiency.

Item								
Identification	Thread	Flow rate (L/min)	A (mm)	B	C (mm)	D (mm)	DN	Size
K- 07 25 10 49	G 1/4	380	47,8	137.0 mm	27,0	110,0	6	1
K- 07 25 10 52	G 1/2	1500	68,8	168.2 mm	34,5	133,7	15	2

## Spare parts

K-HALTERBAUSATZ MULTIFIX	Holder
K-KOPPELPAKET MEHR	Coupling packet
K-KOPPELPAKET SCHMA	Coupling packet
K-PC-BEHAELTER FILTER MULTIFIX	Polycarbonate tank filter
K-METALLBEHAELTER OELER MULTIFIX	Metal tank oiler