
K-FI AK KOH METALLBEHAE MULTIFIX MI

Activated carbon filters with metal bowl



Properties				
Input pressure	Max. 16 bar			
Media temperature	max. 60 °C			
Ambient temperature	Max. 60 °C			
Sealant	NBR			
Filter insert	Activated carbon-POM			
Housing	Die-cast zinc			
Drain valve	Semi-automatic			
Residual oil content	0.005 mg/m3			
Flow rate measurement	FA at P1 = 6 bar and pressure drop Δp = 0.2 bar			





Note

If several devices in the »multifix-mini« Series are assembled together, the maximum working pressure is 12 bar. Further information on request

Description

Micro-filters for compliance with strict compressed air purity requirements. Suitable for all applications where standard filters do not afford the desired efficiency.

Item								
Identification	Thread	Flow rate	Α	В	С	D	DN	Size
		(L/min)	(mm)		(mm)	(mm)		
K- 07 25 10 46	G 1/8	310	40,0	97.3 mm	12,3	85,0	5	0

Spare parts	
K-AUTOMAT ABLASSVENTIL	Automatic drain valve
K-KOPPELPAKET MEHR	Coupling packet
K-ERSATZBEHAELTER MULTI MINI	Spare tank »multifix-mini« & »standard-mini«