

# K-MV O (NO) V 24 V DC H

Normally open, (NO), directly operated, 24 V DC, for high pressures

**HANSA FLEX**

## Properties

|                              |                                                                                                                               |
|------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| <b>Electrical connection</b> | device socket type A in acc. with ISO 4400 for all valves with threads G 3/8 & G 1/2, except valves type 3 & 4. Device socket |
| <b>Thread description</b>    | G thread acc. DIN EN ISO 228-1                                                                                                |
| <b>Media temperature</b>     | max. 80 °C when using water or oils; max. 90 °C when using with air                                                           |
| <b>Protection IP</b>         | IP 65                                                                                                                         |
| <b>Max. working pressure</b> | 20 bar                                                                                                                        |
| <b>Sealant</b>               | FPM                                                                                                                           |
| <b>Housing, valve seat</b>   | Stainless steel 1.4301                                                                                                        |
| <b>Internal parts</b>        | Stainless steel                                                                                                               |



## Note

Further information on request

## Description

Standard series in two different versions: Directly operated, Pilot-operated

| Item           |        |     |           |           |           |      |
|----------------|--------|-----|-----------|-----------|-----------|------|
| Identification | Thread | DN  | A<br>(mm) | B<br>(mm) | C<br>(mm) | Type |
| K- 07 30 01 46 | G 1/8  | 1,5 | 70,0      | 40,0      | 76,0      | 2    |
| K- 07 30 01 47 | G 1/4  | 1,5 | 70,0      | 40,0      | 76,0      | 2    |
| K- 07 30 01 48 | G 3/8  | 3,0 | 85,0      | 52,0      | 92,0      | 2    |
| K- 07 30 01 49 | G 1/2  | 3,0 | 85,0      | 52,0      | 92,0      | 2    |