


| Properties          |                                    |  |  |
|---------------------|------------------------------------|--|--|
| Working pressure    | 10 bar                             |  |  |
| Media temperature   | max. +90 °C                        |  |  |
| Ambient temperature | Max. +90 °C                        |  |  |
| Design              | Blanking screw with hexagon socket |  |  |
| Material            | Brass with a bare metal surface    |  |  |





## Note

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes. Further information on request

## **Additional information**

Further types and dimensions on request.

| Item           |        |            |            |       |  |
|----------------|--------|------------|------------|-------|--|
| Identification | Thread | L1<br>(mm) | L2<br>(mm) | AF    |  |
| K- 07 40 10 22 | G 1/8  | 11,0       | 8,0        | 5 mm  |  |
| K- 07 40 10 23 | G 1/4  | 13,0       | 10,0       | 6 mm  |  |
| K- 07 40 10 24 | G 3/8  | 15,0       | 12,0       | 8 mm  |  |
| K- 07 40 10 25 | G 1/2  | 18,0       | 14,0       | 10 mm |  |
| K- 07 40 45 21 | G 3/4  | 24,0       | 20,0       | 12 mm |  |
| K- 07 40 45 24 | G 1    | 27.0       | 22.0       | 17 mm |  |